

Freestanding Slatwall Stanchions

Style Numbers:

i recotanding statements	Freestanding Slatwall Stanchions		WFCS
--------------------------	----------------------------------	--	------

Features:

For use on worksurfaces/materials that are ¾" to 2" thick
Worksurface/table must be able to support 60 lbs.

Not applicable on bullnose, knife edge or other non-standard table edges

Positions top of Slatwall 15½" above mounting surface; this is a fixed height

Uses only a 2" footprint on the surface

Requires a minimum depth of 18" for table/worksurface stability

Ideal solution for use on height-adjustable worksurfaces or freestanding tables in learning environments, team areas, etc.

Uses standard Slatwall of any length and Worktools

Specify Stanchions and Slatwall separately

Slatwall can overhang Stanchions by 12" for tiles up to 48" wide and 15" for 60" wide tiles

Rubber feet under Stanchions ensure a tight fit without marking surface

Requires 2" clearance under worksurface to accommodate c-clamp

Will not work on a glass surface

Corner application not available

Dimensions / Weight:

W	VFCS	W2" x H16" x D2"	3.50 lbs.

Technical Specifications:

Color:	Black, Champagne, or Platinum	
	Die-cast aluminum for strength and quality consistency. Powder-coat paint process for	
Construction:	durability	
Application:	Mounts to a worksurface or tabletop	
Warranty:	10 years	



For further information, please go to the Steelcase website, steelcase.com or call 888.783.3522

2015 Steelcase Inc. All rights reserved. 6/15