



Tom Dixon

Partner Finish Matrix

Steelcase®

Table of Contents

02 Product Matrix

03 Seating

04 Tables and Desks

05 Finishes

06 Fabrics

12 Hard Surfaces

Seating

	Fabric					Leg/Frame			Seat Cushion
Seating	DIVINA MELANGE 3	GENTLE	HALLINGDAL 65	HERO	MELANGE NAP	BLACK ON OAK	GLOSS BLACK	NATURAL OAK	BLACK LEATHER
Fat Lounge Chair	X	X	X	X	X	X			
Fat Dining Chair	X	X	X	X	X	X			
Fat Stool 75	X	X	X	X	X	X			
Slab Bar Stool						X		X	
Slab Dining Chair						X		X	
Slab Dining Chair Upholstered						X		X	X
Wingback Lounge Chair	X	X	X	X	X		X		
Wingback Micro Chair	X	X	X	X	X		X		

Tables and Desks

	Table Top						Legs/Base				
	Marble		Glass	Oak			Steel		Oak		
Table and Desks	WHITE MARBLE	PEBBLE MARBLE	BRONZE MIRRORRED	BLACK OAK	FUMED OAK	NATURAL OAK	BRUSHED BRASS	BLACK STEEL	BLACK OAK	FUMED OAK	NATURAL OAK
Flash Table Circle			X					X			
Flash Table Rectangle			X					X			
Flash Table Square			X					X			
Screw Cafe Table	X	X						X			
Screw Side Table	X	X						X			
Slab Desk					X	X		X		X	X
Slab Dining Table				X		X			X		X
Tube Table Dining	X	X					X	X			
Tube Table High	X	X					X	X			

Finishes

Fabrics
Hard Surfaces

Fabrics

Divina Melange 3

Technical Specifications
Composition: 100% New Wool | **Durability:** 45,000 Martindale | **Light Fastness:** 6-7 | **Pilling:** 3 (ISO 1-5)
Tests and Certifications: AS/NZS 1530.3, BS 5852 Crib 5, BS 5852 part 1, BS 5867 part 2 type B, IMO FTP Code 2010 Part 8, NF D 60 013, NFPA 260, SN 198 898 5.3 with treatment, UNI 9175 1IM, US Cal. Bull. 117-2013, EN 1021-1/2, EN 13501, C-s1, d0, glued, Chinese GB 50222B1 with treatment, ÖNORM B1/Q1, NFPA 701 with treatment, ASTM E84 Class B Unadhered, ASTM E84 Class A Adhered

Performance Standards
✂ ✂ ✂ Ⓟ

0120*	0147	0170*	0180*	0227*	0237	0260	0277	0280	0367
0427	0457	0467	0471	0517	0527	0547	0557	0567	0571
0581	0587	0617	0620	0647	0677	0687	0731	0747	0757
0777	0787	0821	0871	0917	0937	0967	0977		




*Collection Colors available in 10-12 weeks. All other colorways available in 20-24 weeks.

Fabrics

Gentle

Technical Specifications
Composition: 60% New Wool, 20% Polyester, 20% Nylon | **Durability:** 90,000 Martindale
Light Fastness: 6-7 (ISO 1-8) | **Pilling:** 4-5 (ISO 1-5) | **Tests and Certifications:** BS 5852 crib 5 with treatment, BS 5852 part 1, IMO FTP Code 2010 Part 8, UNI 9175 1IM, US Cal. Bull. 117-2013, DIN 4102 B2, EN 1021-1/2, ASTM E84 Class A Unadhered

Performance Standards
🏠 🧺 🧼 📄

									
0113	0133	0183*	0193*	0203	0223	0373	0443	0553	0573
									
0623	0663	0673	0683	0733	0753	0783*	0873	0933	0963
									
0973*									

















*Collection Colors available in 10-12 weeks. All other colorways available in 20-24 weeks.

Fabrics

Hallingdal 65

Technical Specifications
Composition: 70% New Wool, 30% Viscose | **Durability:** 100,000 Martindale | **Light Fastness:** 7
Pilling: 3-4 (ISO 1-5) | **Tests and Certifications:** AS/NZS 1530.3, BS 5852 Crib 5, BS 5852 part 1, IMO FTP Code 2010 Part 8, NF D 60 013, NFPA 260, UNI 9175 1IM, US Cal. Bull. 117-2013, EN 1021-1/2, SN 198 898 5.2 with treatment, AS/NZS 3837 class 2, ÖNORM B1/Q1, ASTM E84 Class A Adhered, ASTM E84 Class B Unadhered, GB 50222 B1 with treatment (Chinese)

Performance Standards
✶ ✷ ✸ ⓘ

									
0100	0103	0110	0113	0116*	0123	0126	0130*	0143	0153
									
0166	0173	0180*	0190*	0200	0220	0224	0227	0270	0350
									
0368	0370	0376	0390	0407	0420	0457	0526	0547	0563
									
0573	0590	0596	0600	0657	0660	0674	0680	0687	0694












*Collection Colors available in 10-12 weeks. All other colorways available in 20-24 weeks.

Fabrics

Hallingdal 65

Technical Specifications
Composition: 70% New Wool, 30% Viscose | **Durability:** 100,000 Martindale | **Light Fastness:** 7
Pilling: 3-4 (ISO 1-5) | **Tests and Certifications:** AS/NZS 1530.3, BS 5852 Crib 5, BS 5852 part 1, IMO FTP Code 2010 Part 8, NF D 60 013, NFPA 260, UNI 9175 1IM, US Cal. Bull. 117-2013, EN 1021-1/2, SN 198 898 5.2 with treatment, AS/NZS 3837 class 2, ÖNORM B1/Q1, ASTM E84 Class A Adhered, ASTM E84 Class B Unadhered, GB 50222 B1 with treatment (Chinese)

Performance Standards
🏠 🏢 🏡 🏠




















									
0702	0723	0733	0750	0753	0754	0763	0764	0773	0810
									
0840	0850	0890	0907	0944	0960	0968	0980		

Fabrics

Hero

Technical Specifications
Composition: 96% New Wool, 4% Nylon | **Durability:** 45,000 Martindale | **Light Fastness:** 5-6
Pilling: 3-4 (ISO 1-5) | **Tests and Certifications:** BS 5852 crib 5 with treatment, BS 5852 part 1, IMO FTP Code 2010 Part 7 with treatment, IMO FTP Code 2010 Part 8, NF D 60 013, SN 198 898 5.3 with treatment, UNI 9175 1IM, US Cal. Bull. 117-2013, EN 1021-1/2, NFPA 701 with treatment, AS/NZS 3837 class 2, ASTM E84 Class B Adhered, ASTM E84 Class A Unadhered


Performance Standards
☒ ☒ ☒ ☒

						
0101	0141	0151	0181	0191*	0201	0211*
						
0231	0311	0381	0411	0441	0451	0481
						
0511*	0541	0551	0601	0681	0701	0711
						
0751	0791	0901	0931	0941	0981	0991*

*Collection Colors available in 10-12 weeks. All other colorways available in 20-24 weeks.

Leather

Technical Specifications
Leather Type: Semi-aniline, Full Grain
Durability: < 4 scale, Dry rub 500 cycles, EN ISO 11640
Light Fastness: < 4 Value 8 Blu scale, ISO 105-B02
Tannage: Chrome Tanned
Country of Origin: Italy
Tests and Certifications: TB 117-2013



Leather

Fabrics

Melange Nap

Technical Specifications
Composition: 97% New Wool, 3% Nylon | **Durability:** 60,000 Martindale | **Light Fastness:** 6 (ISO 1-8)
Pilling: 3-4 (ISO 1-5) | **Tests and Certifications:** BS 5852 crib 5 with treatment, BS 5852 part 1, IMO FTP Code 2010 Part 8, NF D 60 013, UNI 9175 1IM, US Cal. Bull. 117-2013, EN 1021-1/2, ASTM E84 Class B Adhered, ASTM E84 Class A Unadhered, AS/NZS 3837 class 2, SN 198 898 5.3 with treatment

Performance Standards
🔪 🧼 🧺 📄

0111*	0171	0191*	0211	0221	0241	0271	0321	0351	0371
0411	0441	0461	0491*	0521	0551	0651	0691	0711	0751
0771	0791*	0871	0911	0951	0991				

*Collection Colors available in 10-12 weeks. All other colorways available in 20-24 weeks.

Hard Surfaces

Glass



Bronzed Mirror

Marble



Pebble Marble



White Marble

Oak



Black Oak



Fumed Oak




Natural Oak

Steel



Black Steel



Brushed Brass

